

SAFETY DATA SHEET

Diesel Cold Flow Improver

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Diesel Cold Flow Improver

Product no.: 907052

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Additive

Use descriptors (UK REACH):

Product

Product category	Description
	Additives to petrol or diesel fuel

Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Rymax Lubricants

Delweg 8

6902 PJ Zevenaar The Netherlands +31 (0) 316 740 856

www.rymax-lubricants.com Product Safety Department

info@rymax-lubricants.com

Revision: 20/07/2023

SDS Version: 1.0

1.4. Emergency telephone number

Contact person:

E-mail:

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

STOT SE 3; H336, May cause drowsiness or dizziness.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s):



Signal word: Dange



Hazard statement(s): May be fatal if swallowed and enters airways.

(H304)

May cause drowsiness or dizziness. (H336) May cause damage to organs through prolonged or repeated exposure. (H373) Toxic to aquatic life with long lasting effects.

(H411)

Precautionary statement(s):

General: Keep out of reach of children. (P102)

Prevention: Do not breathe vapour/mist. (P260)

Avoid release to the environment. (P273)

Response: IF SWALLOWED: Immediately call a POISON

CENTER/doctor. (P301+P310)

Get medical advice/attention if you feel

unwell. (P314)

Storage: -

Disposal: Dispose of contents/container in accordance

with local regulation (P501)

Hazardous substances: Hydrocarbons, C10, aromatics, <1%

naphthalene

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Additional labelling: EUH208, Contains reaction mass of:

2,2',2"',2"'-(ethylenedinitrilotetrakis-N,N-

di(C16)alkylacetamide;2,2',2'',2'''- (ethylenedinitrilotetrakis-N,N-

di(C18)alkylacetamide. May produce an

allergic reaction.

2.3. Other hazards

Additional warnings: This mixture/product does not contain any

substances considered to meet the criteria classifying them as PBT and/or vPvB. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU)

2017/2100 or Commission Regulation (EU)

2018/605.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C10,	CAS No.:	95-100%	EUH066	
aromatics, <1%	EC No.: 918-811-1		Asp. Tox. 1, H304	



Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended S.I. 2019 No. 758

naphthalene	UK-REACH: Index No.:		STOT SE 3, H336 Aquatic Chronic 2, H411	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	CAS No.: EC No.: 925-653-7 UK-REACH: Index No.:	1-3%	EUH066 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	CAS No.: 64742-82-1 EC No.: 919-164-8 UK-REACH: Index No.:	1-3%	Asp. Tox. 1, H304 STOT RE 1, H372 Aquatic Chronic 3, H412	[19]
reaction mass of: 2,2',2",2"'- (ethylenedinitrilotetrakis- N,N- di(C16)alkylacetamide;2,2' ,2",2"'- (ethylenedinitrilotetrakis- N,N- di(C18)alkylacetamide	CAS No.: 136920-07-5 EC No.: 406-640-0 UK-REACH: Index No.: 616-047-00-0	<1%	Skin Sens. 1B, H317	
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5 UK-REACH: Index No.: 601-052-00-2	<0.05%	Flam. Sol. 2, H228 Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

4.1.	Descri	ption o	f first aic	l measures
------	--------	---------	-------------	------------

General information: In the case of accident: Contact a doctor or

casualty department – take the label or this

safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist.

Never give an unconscious person water or

other drink.

Inhalation: Upon breathing difficulties or irritation of the

respiratory tract: Bring the person into fresh

air and stay with him/her.

Skin contact: Remove contaminated clothing and shoes

immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin

Diesel Cold Flow Improver Page 3 of 14



cleanser can be used. DO NOT use solvents

or thinners.

If skin irritation occurs: Get medical

advice/attention.

Eye contact: If in eyes: Flush eyes with water or saline

water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during

transport.

Ingestion: IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical

pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical

attention for at least 48 hours.

Burns: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3Z



SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material: Keep only in original packaging.

Storage temperature: Dry, cool and well ventilated

Store out of direct sunlight.

Incompatible materials: Strong acids, strong bases, strong oxidizing

agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

DNEL

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m³
Long term – Local effects - Workers	Inhalation	837.5 mg/m ³



Long term – Systemic effects - General population	Inhalation	410 μg/m³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m³
Short term – Local effects - General population	Inhalation	640 mg/m³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m ³
Short term – Systemic effects - General population	Inhalation	1152 mg/m³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m ³

naphthalene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	3,57 mg/kgbw/day
Long term – Systemic effects - Workers	Inhalation	25 mg/m³

PNEC

naphthalene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,0024 mg/L
Marine water		0,0024 mg/L

8.2. Exposure controls

Control is unnecessary if the product is used as intended.

General recommendations: Smoking, drinking and consumption of food

is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios

implemented for this product.

Exposure limits: Occupational exposure limits have not been

defined for the substances in this product.

Appropriate technical measures: Apply standard precautions during use of the

product. Avoid inhalation of vapours.

Hygiene measures: In between use of the product and at the end

of the working day all exposed areas of the body must be washed thoroughly. Always

wash hands, forearms and face.

Measures to avoid environmental exposure: Keep damming materials near the workplace.

If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:

Туре	Class	Colour	Standards	
No special when used as intended.				

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	R

Hand protection:

Diesel Cold Flow Improver Page 6 of 14



Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended S.I. 2019 No. 758

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,38	> 240	EN374-2, EN374-3, EN388	

Eye protection:

Туре	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Yellowish
Odour / Odour threshold: Characteristic

pH: No data available

Density (g/cm³): 0.8887

Relative density: No data available Kinematic viscosity: No data available

Particle characteristics: Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C):

Testing not relevant or not possible due to

the nature of the product.

Softening point/range (waxes and pastes) (°C): Does not apply to liquids.

Boiling point (°C): >160

Vapour pressure:0.6 hPa (20 °C)Relative vapour density:No data availableDecomposition temperature (°C):No data available

Data on fire and explosion hazards

Flash point (°C): >61

Flammability (°C):

Auto-ignition temperature (°C):

No data available

Lower and upper explosion limit (% v/v): 0.6 - 7

Solubility

Solubility in water: Insoluble

*n-octanol/water coefficient:*No data available
Solubility in fat (g/L):
No data available

9.2. Other information

Oxidizing properties:

Other physical and chemical parameters:

No data available.

Diesel Cold Flow Improver Page 7 of 14



SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Product/substance naphthalene
Test method: OECD 403
Species: Rat
Route of exposure: Inhalation
Test: LC50
Result: >0,4 mg/L

Product/substance naphthalene
Test method: OECD 402
Species: Rat
Route of exposure: Dermal
Test: LD50

Result: >16000 mg/kg

Product/substance naphthalene
Test method: OECD 401
Species: Mouse
Route of exposure: Oral
Test: LD50
Result: 533 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized



persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Product/substance naphthalene

Species: Rat

Route of exposure: Inhalation

Target organ:

Duration: 24 months Test: NOAEL

Result:

Conclusion: Adverse effect observed

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

Not applicable.

Other information

naphthalene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Product/substance naphthalene

Species: Algae, Pseudokirchneriella subcapitata

Duration: 96 hours
Test: EC50
Result: 2,96 mg/L

Product/substance naphthalene

Species: Daphnia, Daphnia magna

Duration: 48 hours
Test: EC50
Result: 2,16 mg/L

Product/substance naphthalene

Species: Fish, Oncorhynchus gorbuscha

Duration: 96 hours
Test: LC50
Result: 0,96 mg/L

Product/substance naphthalene

Species: Daphnia, Daphnia pulex



Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended S.I. 2019 No. 758

Duration: 125 days
Test: NOEC
Result: 0,59 mg/L

Product/substance naphthalene

Species: Fish, Oncorhynchus gorbuscha

Duration: 40 days
Test: NOEC
Result: 0,12 mg/L

12.2. Persistence and degradability

Product/substance naphthalene

Biodegradable: No

Test method:

Result: 0 to 2 % - Not readily - 28 days

12.3. Bioaccumulative potential

Product/substance naphthalene

Test method:

Potential No data available.

bioaccumulation:

LogPow: 36.5-168 BCF: 3,4

Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.



SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics, > 1% naphthalene)	Transport hazard class: 9 Label: 9 Classification code: M6	III	Yes	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics, > 1% naphthalene)	Transport hazard class: 9 Label: 9 Classification code: M6	III	Yes	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrocarbons, C10, aromatics, > 1% naphthalene)	Transport hazard class: 9 Label: 9 Classification code: M6	III	Yes	See below for additional information.

^{*} Packing group

Additional information

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●3Z

Diesel Cold Flow Improver

^{**} Environmental hazards



14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: People under the age of 18 shall not be

exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate

exposure, must be considered.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances: E2 - ENVIRONMENTAL HAZARDS, Qualifying

quantity (lower-tier): 200 tonnes / (upper-

tier): 500 tonnes

Additional information: Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources: The Management of Health and Safety at

Work Regulations 1999.

The Health and Safety at Work etc. Act 1974

Regulations 2013.

Control of Major Accident Hazards (COMAH)

Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and

amended in UK law.

Regulation (EC) No 1272/2008 on

classification, labelling and packaging of substances and mixtures (CLP) as retained

and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained

and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H228, Flammable solid.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.



H317, May cause an allergic skin reaction.

H336, May cause drowsiness or dizziness.

H351, Suspected of causing cancer.

H372, Causes damage to organs through prolonged or repeated exposure.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

= Additives to petrol or diesel fuel

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations


UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.





The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products. It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en