

SAFETY DATA SHEET

Engine Flush

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Engine Flush
Product no.: 907090-502643

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Additive
Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Rymax Lubricants**
Delweg 8
6902 PJ Zevenaar
The Netherlands
+31 (0) 316 740 856
www.rymax-lubricants.com
Contact person: Product Safety Department
E-mail: info@rymax-lubricants.com
Revision: 20/07/2023
SDS Version: 1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).
See section 4 "First aid measures".

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.2. Label elements

Hazard pictogram(s): Not applicable.
Signal word: Not applicable.
Hazard statement(s): Not applicable.
Precautionary statement(s):
General: -
Prevention: -
Response: -

<i>Storage:</i>	-
<i>Disposal:</i>	-
<i>Hazardous substances:</i>	None known.
<i>Additional labelling:</i>	EUH208, Contains Phenol, C14-18-alkyl derivs.. May produce an allergic reaction. EUH210, Safety data sheet available on request.

2.3. Other hazards

<i>Additional warnings:</i>	This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.
-----------------------------	---

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	CAS No.: 64742-65-0 EC No.: 265-169-7 UK-REACH: Index No.: 649-474-00-6	75-100%	Asp. Tox. 1, H304	[12]
Phenol, C14-18-alkyl derivs.	CAS No.: 1190625-94-5 EC No.: 931-468-2 UK-REACH: Index No.:	<0.25%	Skin Sens. 1B, H317 STOT RE 2, H373	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[12] The classification as a carcinogen will not be taken into account as the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method' (CLP, Annex VI, note L).

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion:

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns:

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Always store in containers of the same material as the original container.

Storage temperature:

Dry, cool and well ventilated
<40°C

Incompatible materials:

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

DNEL

Phenol, C14-18-alkyl derivs.

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	300 µg/kgbw/day
Long term – Systemic effects - Workers	Inhalation	1.17 mg/m ³

PNEC

Phenol, C14-18-alkyl derivs.

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		100 µg/L
Freshwater sediment		4266.16 mg/kg
Intermittent release (freshwater)		1 mg/L
Marine water		10 µg/L
Marine water sediment		426.62 mg/kg
Predators		3.3 mg/kg
Sewage treatment plant		100 mg/L
Soil		852.58 mg/kg

8.2. Exposure controls

Control is unnecessary if the product is used as intended.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures:

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures:

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure:

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally:

Use only UKCA marked protective equipment.



Respiratory Equipment:

No specific requirements

Skin protection:

No specific requirements.

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile/Neoprene	0,65	> 240	EN374-2, EN374-3, EN388	
Vinyl/PVC	>0.35	> 480	EN374-3, EN388	

Eye protection:
No specific requirements.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Tan
<i>Odour / Odour threshold:</i>	Characteristic
<i>pH:</i>	Not applicable
<i>Density (g/cm³):</i>	0.873 (15 °C)
<i>Kinematic viscosity:</i>	32.2 mm ² /s (40 °C)
<i>Particle characteristics:</i>	Not applicable - product is a liquid

Phase changes

<i>Melting point/Freezing point (°C):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Softening point/range (waxes and pastes) (°C):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available
<i>Decomposition temperature (°C):</i>	Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

<i>Flash point (°C):</i>	>200
<i>Flammability (°C):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Auto-ignition temperature (°C):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Lower and upper explosion limit (% v/v):</i>	Testing not relevant or not possible due to the nature of the product.

Solubility

<i>Solubility in water:</i>	Insoluble
<i>n-octanol/water coefficient:</i>	No data available
<i>Solubility in fat (g/L):</i>	Testing not relevant or not possible due to the nature of the product.

9.2. Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Oxidizing properties:</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kgbw

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>5000 mg/kg

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	>5,53 mg/l/4h

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rat
Route of exposure:	Oral
Target organ:	
Duration:	90 days
Test:	LOAEL
Result:	125 mg/kgbw
Conclusion:	No adverse effect observed

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rat
Route of exposure:	Dermal
Target organ:	
Duration:	90 days
Test:	NOAEL

Result: 1000 mg/kgbw
Conclusion: No adverse effect observed

Aspiration hazard

Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Kin. viscosity (mm²/s): 32,2
Test:
Conclusion: Aspiration hazard not applicable
Other information:

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

Not applicable.

Other information

None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species: Fish, Pimephales promelas
Duration:
Test: LC50
Result: >100 mg/L

Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species: Crustacean, Daphnia magna
Duration:
Test: EC50
Result: >10000 mg/L

Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species: Fish, Oncorhynchus mykiss
Duration:

Test:	NOEC
Result:	1000 mg/L
Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Crustacean, Daphnia magna
Duration:	
Test:	NOEC
Result:	10 mg/L
Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	
Test:	NOEC
Result:	>100 mg/L

12.2. Persistence and degradability

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Biodegradable:	No
Test method:	OECD 301 F
Result:	31% 28d

12.3. Bioaccumulative potential

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Test method:	
Potential bioaccumulation:	No data available.
LogPow:	9,2
BCF:	260
Other information:	

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

Restricted to professional users.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances:

Not applicable.

Additional information:

Not applicable.

Sources:

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H304, May be fatal if swallowed and enters airways.

H317, May cause an allergic skin reaction.

H373, May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWG = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en