

SAFETY DATA SHEET

Rymax Diesel Treatment 1:1000

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Rymax Diesel Treatment 1:1000

Product no.

5114700

Unique formula identifier (UFI)

F6NJ-X4D9-G00T-TS0D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Additive

Use descriptors (REACH)

| Product category | Description | |
|------------------|--------------|--|
| PCO | Other produc | |

▼ Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Rymax Lubricants

Delweg 8

6902 PJ Zevenaar

The Netherlands

+31 (0) 316 740 856

www.rymax-lubricants.com

Contact person

Product Safety Department

info@rymax-lubricants.com

Revision

24/01/2023

SDS Version

Date of previous version

09/09/2022 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Acute Tox. 4; H302, Harmful if swallowed.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Acute Tox. 4; H332, Harmful if inhaled.

Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)









Signal word

Danger

Hazard statement(s)

Harmful if swallowed or if inhaled. (H302+H332) May be fatal if swallowed and enters airways. (H304) Toxic to aquatic life with long lasting effects. (H411)

Safety statement(s)

General

Keep out of reach of children. (P102)

Prevention

Use only outdoors or in a well-ventilated area. (P271)

Avoid breathing mist/vapour. (P261)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310) Do NOT induce vomiting. (P331)

Storage

_

▼ Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2-ethylhexyl nitrate

2-ethylhexan-1-ol

Hydrocarbons, C10, aromatics, <1% naphthalene

▼Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: F6NJ-X4D9-G00T-TS0D

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. ▼ Substances

Not applicable. This product is a mixture.

3.2. Mixtures

| Product/substance | Identifiers | % w/w | Classification | Note |
|---|---|--------|---|------|
| Hydrocarbons, C10-C13, n- alkanes, isoalkanes, cyclics, <2% aromatics | CAS No.: EC No.: 918-481-9 UK-REACH: Index No.: | 40-60% | EUH066 Asp. Tox. 1, H304 | |
| 2-ethylhexyl nitrate | CAS No.: 27247-96-7 EC No.: 248-363-6 UK-REACH: Index No.: | 25-40% | EUH044 EUH066 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Chronic 2, H411 | |
| 2-ethylhexan-1-ol | CAS No.: 104-76-7 EC No.: 203-234-3 UK-REACH: Index No.: | 1-3% | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 | [1] |



Hydrocarbons, C10, CAS No.: 1-3% EUH066

aromatics, <1% naphthalene EC No.: 918-811-1

 EC No.: 918-811-1
 Asp. Tox. 1, H304

 UK-REACH:
 STOT SE 3, H336

 Index No.:
 Aquatic Chronic 2, H411

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO2)

5.3. Advice for firefighters



Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

Store out of direct sunlight.

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Long term exposure limit (8 hours) (ppm): 184

Long term exposure limit (8 hours) (mg/m³): 1200

2-ethylhexan-1-ol

Long term exposure limit (8 hours) (ppm): 1

Long term exposure limit (8 hours) (mg/m³): 5,4

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

2-ethylhexan-1-ol

| Duration | Route of exposure | DNEL | |
|----------|-------------------|------|--|
|----------|-------------------|------|--|



| Long term – Systemic effects - General population | Dermal | 11.4 mg/kg bw/day |
|---|------------|------------------------|
| Long term – Systemic effects - Workers | Dermal | 23 mg/kg bw/day |
| Long term – Local effects - General population | Inhalation | 26.6 mg/m ³ |
| Long term – Local effects - Workers | Inhalation | 53.2 mg/m ³ |
| Long term – Systemic effects - General population | Inhalation | 2.3 mg/m ³ |
| Long term – Systemic effects - Workers | Inhalation | 12.8 mg/m ³ |
| Short term – Local effects - General population | Inhalation | 26.6 mg/m ³ |
| Short term – Local effects - Workers | Inhalation | 53.2 mg/m³ |
| Long term – Systemic effects - General population | Oral | 1.1 mg/kg bw/day |

2-ethylhexyl nitrate

| Duration | Route of exposure | DNEL |
|---|-------------------|-----------------|
| Long term – Local effects - General population | Dermal | 22 μg/cm² |
| Long term – Local effects - Workers | Dermal | 44 μg/cm² |
| Long term – Systemic effects - General population | Dermal | 520 μg/kgbw/day |
| Long term – Systemic effects - Workers | Dermal | 1 mg/kg bw/day |
| Long term – Systemic effects - General population | Inhalation | 87 μg/m³ |
| Long term – Systemic effects - Workers | Inhalation | 350 μg/m³ |
| Long term – Systemic effects - General population | Oral | 25 μg/kgbw/day |

▼ PNEC

2-ethylhexan-1-ol

| Route of exposure | Duration of Exposure | PNEC |
|-----------------------------------|-----------------------------|------------|
| Freshwater | | 17 μg/L |
| Freshwater sediment | | 284 μg/kg |
| Intermittent release (freshwater) | | 170 μg/L |
| Marine water | | 1.7 μg/L |
| Marine water sediment | | 28.4 μg/kg |
| Predators | | 55 mg/kg |
| Sewage treatment plant | | 10 mg/L |
| Soil | | 47 μg/kg |
| | | |

2-ethylhexyl nitrate

| 2-etriyine xyr mit ate | | |
|------------------------|-----------------------------|-----------|
| Route of exposure | Duration of Exposure | PNEC |
| Freshwater | | 800 ng/L |
| Freshwater sediment | | 740 ng/kg |
| Marine water | | 80 ng/L |
| Marine water sediment | | 740 ng/kg |
| Sewage treatment plant | | 10 mg/L |
| Soil | | 191 ng/kg |
| | | |

8.2. ▼Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.



▼Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

8.3. Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

| Туре | Class | Colour | Standards | |
|---|--------|--------|-----------|--|
| Respiratory pr is not needed event of adequ | in the | | | |
| ventilation | | | | |

Skin protection

| till protection | | | |
|--|---------------|-----------|--|
| Recommended | Type/Category | Standards | |
| Dedicated work clothing should be worn | - | - | |



Hand protection

| Material | Glove thickness (mm) | Breakthrough time (min.) | Standards | |
|----------|----------------------|-----------------------------|-------------------------|--|
| Nitrile | 0,38 | > 240 | EN374-2, EN374-3, EN388 | |



Eye protection

| Туре | Standards |
|-----------------------------------|-----------|
| Safety glasses with side shields. | EN166 |



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear

Odour / Odour threshold

Characteristic

Testing not relevant or not possible due to nature of the product.

Density (q/cm3)

0.854 (20 °C)

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)



No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

160-245

Vapour pressure

<0.1 kPa (20 °C)

Relative vapour density

No data available

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

>61

Auto-Ignition (°C)

No data available

Flammability (°C)

>200

Lower and upper explosion limit (% v/v)

0.6 - 7

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (q/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

0.04

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. ▼ Possibility of hazardous reactions

None known.

10.4. ▼ Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method OECD 403
Species Rat
Route of exposure Inhalation
Test LC50 (4 hours)
Result >5000 mg/m³



Other information

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method OECD 401
Species Rat
Route of exposure Oral
Test LD50

Result >5000 mg/kg

Other information

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method OECD 402
Species Rabbit
Route of exposure Dermal
Test LD50
Result >5000 mg/kg

Other information

Harmful if swallowed. Harmful if inhaled.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

▼ Long term effects

None known.

▼ Endocrine disrupting properties

None known.

▼ Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance Test method

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Species

Daphnia, Daphnia magna

Compartment

Duration 48 hours
Test EL0

Result 1000 mg/L

Other information

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics



Test method

Species Fish, Oncorhynchus mykiss

Compartment

Duration 96 hours
Test LL0
Result 1000 mg/L

Other information

Product/substance

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Test method Species

Algae, Pseudokirchneriella subcapitata

Compartment

Duration 72 hours
Test EL0
Result 1000 mg/L

Other information

12.2. Persistence and degradability

Product/substance Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradable Yes
Test method OECD 301 F
Result >60%

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. ▼ Endocrine disrupting properties

None known.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 6 - Acute toxicity

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

| | 14.1 UN / ID | 14.2 UN proper shipping name | 14.3 Hazard class(es) | 14.4 PG* | 14.5 Env** | Other information |
|-----|-----------------|--|---|-------------|---------------|---|
| ADR | UN3082 | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | Class: 9 Labels: 9 Classification code: M6 | III | Yes | Limited quantities: 5 L Tunnel restriction code: (-) |



| | 14.1 UN / ID | 14.2 UN proper shipping name | 14.3 Hazard class(es) | 14.4 PG* | 14.5 Env** | Other information |
|------|-----------------|--|--|-------------|---------------|---|
| | | | | | | See below for additional information. |
| IMDG | UN3082 | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | Class: 9 Labels: 9 Classification code: M6 | III | Yes | Limited quantities: 5 L EmS: F-A S-F See below for additional information. |
| IATA | UN3082 | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | Class: 9 Labels: 9 Classification code: M6 | III | Yes | See below for additional information. |

^{*} Packing group

** Environmental hazards

▼Additional information

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼ Restrictions for application

None known.



Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

▼ Additional information

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH044, Risk of explosion if heated under confinement.

EUH066, Repeated exposure may cause skin dryness or cracking.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

PC0 = Other products

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail



RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

▼ The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en