



# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 10/13/2022 Revision date: 4/14/2023 Supersedes version of: 10/13/2022 Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : LUB007001 - Rymax Helios XT 20W-50  
Product code : LUB007001

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Rymax Lubricants B.V.  
Delweg, 8  
NL- 6902 PJ Zevenaar – Netherlands  
Netherlands  
T tel: +31 (0) 316 740 856  
[info@rymax-lubricants.com](mailto:info@rymax-lubricants.com) - [www.rymax-lubricants.com](http://www.rymax-lubricants.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0) 316 740 856

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

#### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 75 – < 90	Not classified
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	≥ 1 – < 5	Not classified
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	≥ 0.3 – < 3	Not classified
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	EC-No.: 701-251-5 REACH-no: 01-2119524004-56	≥ 0.3 – < 3	Aquatic Chronic 4, H413
Distillates (petroleum), solvent-refined heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64741-88-4 EC-No.: 265-090-8 EC Index-No.: 649-454-00-7 REACH-no: 01-2119488706-23	≥ 0.3 – < 3	Not classified

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Precautionary measures fire : Exercise caution when fighting any chemical fire.  
Firefighting instructions : Use water spray or fog for cooling exposed containers.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and gloves.  
Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Ensure good ventilation of the work station. Wear personal protective equipment.  
Handling temperature : ≤ 40 °C  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Provide local exhaust or general room ventilation.
Storage conditions	: Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 40 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Keep only in original container. Store in a closed container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		EN ISO 374

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: petroleum-like odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -27 °C ASTM D7346
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 220 °C ASTM D92
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 133 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
Solubility	: insoluble in water.

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 866 kg/m <sup>3</sup> @ 15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (mg/l)	> 5000 mg/l/4h
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50

LD50 oral (rat)	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal (rabbit)	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation (rat) (mg/l)	> 1.67 mg/l OECD 403 (1h)

### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (mg/l)	> 5000 mg/m <sup>3</sup>
LC50 inhalation (rat) (Vapours - mg/l/4h)	5.53 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
----------------------------	---

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

### Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50

NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

Aspiration hazard	: Not classified
-------------------	------------------

### LUB007001 - Rymax Helios XT 20W-50

Viscosity, kinematic	133 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
----------------------	--

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	98 (98 – 108) mm <sup>2</sup> /s @40°C
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Viscosity, kinematic	150 (1.99 – 847) mm <sup>2</sup> /s @40°C
<b>Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50</b>	
Viscosity, kinematic	206820 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'cSt'
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s @40°C
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
Viscosity, kinematic	28.51 mm <sup>2</sup> /s @40°C

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d)
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50</b>	
LC50 - Fish [1]	> 1000 mg/l Source: ECHA Chem
EC50 - Crustacea [1]	> 1000 mg/l Source: ECHA Chem



# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

**Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50**

EC50 96h - Algae [1]	> 1000 mg/l Green algae ( <i>Selenastrum capricornutum</i> )
----------------------	--

### **Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)**

LC50 - Fish [1]	> 100 mg/l <i>Pimephales promelas</i>
EC50 - Crustacea [1]	> 10000 mg/l <i>Daphnia magna</i>
NOEC chronic fish	1000 mg/l <i>Oncorhynchus mykiss</i> (14d)
NOEC chronic crustacea	10 mg/l <i>Daphnia magna</i> (21d)
NOEC chronic algae	≥ 100 mg/l <i>Pseudokirchneriella subcapitata</i> (72h)

### **Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)**

LC50 - Fish [1]	> 100 mg/l <i>Pimephales promelas</i>
EC50 - Crustacea [1]	> 10000 mg/l <i>Daphnia magna</i>
NOEC chronic fish	1000 mg/l <i>Oncorhynchus mykiss</i> (14d)
NOEC chronic crustacea	10 mg/l <i>Daphnia magna</i> (21d)
NOEC chronic algae	≥ 100 mg/l <i>Pseudokirchneriella subcapitata</i> (72h)

## 12.2. Persistence and degradability

### **Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)**

Persistence and degradability	Not readily biodegradable.
Biodegradation	< 60 % OECD 301F (28d)

### **Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)**

Biodegradation	31 % OECD 301F (28d)
----------------	----------------------

**Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50**

Persistence and degradability	Not readily biodegradable.
Biodegradation	4.7 – 10.8 % OECD TG 301 B (28d)

### **Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)**

Biodegradation	31 % OECD 301F (28d)
----------------	----------------------

### **Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)**

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD 301F (28d)

## 12.3. Bioaccumulative potential

### **Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)**

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6
---	---------

### **Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)**

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

**Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50**

Bioconcentration factor (BCF REACH)	2.2
Partition coefficient n-octanol/water (Log Kow)	11.08

**Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)**

Partition coefficient n-octanol/water (Log Pow)	> 6
---	-----

**Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)**

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6
---	---------

### 12.4. Mobility in soil

**Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50**

Mobility in soil	3615000000000 Source: EPISUITE
------------------	--------------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Added	
	Revision date	Modified	
1.2	Main use category	Modified	
3	Composition/information on ingredients	Modified	
5.1	Unsuitable extinguishing media	Added	
5.3	Firefighting instructions	Added	
5.3	Precautionary measures fire	Added	
6.1	Protective equipment	Added	
6.3	For containment	Added	
7.1	Handling temperature	Added	
7.1	Precautions for safe handling	Modified	
7.2	Special rules on packaging	Added	
7.2	Storage area	Added	
7.2	Storage temperature	Added	
7.2	Technical measures	Added	
8.2	Personal protective equipment	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

# LUB007001 - Rymax Helios XT 20W-50

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
H413	May cause long lasting harmful effects to aquatic life.

Safety Data Sheet (SDS), EU RYMAX 2023

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.